

Technical Datasheet	BTNBCG003/PG
Product Description	Waterproof Brass Cable Glands
Product Range	Cable Gland-Brass (PG Threads)

BEISIT

1 Tangmei Rd.,Yuhang Economic-
Technological Development
Area, Hangzhou, Zhejiang 311100, China
Tel:0086 571 8936 2885
Web:www.beisit.com

Standard PG Brass Cable Glands


Standards: EN 50262

Protection: IP68

Temperature Range: -40°C to 100°C (static)

Material (Gland): Nickel-Plated Brass

Material Seal: NBR



Model	Cable Range	H	GL	Spanner Size	Beisit No.
mm	mm	mm	mm		
PG7	3-6,5	19	5	14	P0707BR
PG7	2-5	19	5	14	P0705BR
PG9	4-8	21	6	17	P0908BR
PG9	2-6	21	6	17	P0906BR
PG11	5-10	22	6	20	P1110BR
PG11	3-7	22	6	20	P1107BR
PG13.5	6-12	24	6,5	22	P13512BR
PG13.5	5-9	24	6,5	22	P13509BR
PG16	10-14	23	6,5	24	P1614BR
PG16	7-12	23	6,5	24	P1612BR
PG21	13-18	24	7	30	P2118BR
PG21	9-16	24	7	30	P2116BR
PG29	18-25	29	8	40	P2925BR
PG29	13-20	29	8	40	P2920BR
PG36	22-32	35	8	50	P3632BR
PG36	20-26	35	8	50	P3626BR
PG42	32-38	37	9	57	P4238BR
PG42	25-31	37	9	57	P4231BR
PG48	37-44	38	10	64	P4844BR
PG48	29-35	38	10	64	P4835BR

- Standard Metric range of Brass cable glands.
- Atmospheric Membrane - Seals and protects.
- Unique O ring Structure between Body and Claw - Excellent Waterproof Guarantee

Factory Approvals & Accreditation

